

# The PuriGator™ Fluid Purifier

with Grease Gator Technology



## Specifications:

Pump electrical requirement: 120V/60 Hz/ less than 1 amp; 30 gallon purification vessel is 28 1/2 inch tall, 19 inch diameter; durable polymer construction; easy to empty used oil collection reservoir; gravity-powered fluid return; 1-year warranty including replacement parts with extendable warranty and service plans available.



## Skimmer Options:

Float Type	Small Crown	Large Crown	T
Pump Size	Submersible 3 gpm Hangover 5 gpm	Submersible 5 gpm Hangover 10 gpm	Submersible 5 gpm Hangover 10 gpm
Temperature Tolerance	Submersible 115° F Hangover 160° F*	Submersible 115° F Hangover 160° F*	Submersible 115° F Hangover 160° F*
Minimum Fluid Depth	6 inches	7 inches	4 inches
Fluid Depth Fluctuation Tolerance (maximum)	+/- 3 inches	+/- 4 inches	+/- 12+ inches
Foam Tolerance	Weak	Weak	Strong
Surface Area (footprint) required in tank	Submersible 3"X8" Hangover 3"X4"	Submersible 4"X10" Hangover 4"X6"	8"X16" to 8"X32+"
Skimming Requirement	Medium	High	Low
Bacteria Free Option with Predator™	Yes	Yes	Yes
Collect Used Oil for Recycling or Reuse	Yes	Yes	Yes

\* High Temperature applications (>115° F) require CPVC materials for floats and fittings.