

Offer Packet

Product	Glycerin
COA & SDS	Included below

If interested, please call or email:

Steve Rundell

Solvent Systems International

70 King St.

Elk Grove Village, IL 60007

847437-1100 x 1800

srundell@solvent-systems.com

www.solvent-systems.com



PRODUCT SPECIFICATION

Glycerin, Biodiesel Derived Feed Grade (AAFCO IFN T60.111)

Specifications:

Feedstock	Mixed
Glycerin, wt% min.	80.0
Water, wt% max.	14.0
Methanol, max.	1500 ppm
Ash, wt% max.	8.0
MONG, wt% max.	4.0

CAUTION: Intended use of this product is for further mixing into livestock feed, or other industrial processes. Do not to exceed 15% of the complete feed for ruminants and 10% of the complete feed for all other livestock species, including poultry.

Certificate of Analysis

Glycerin

Analysis				
Parameter	Method		Units	Limit
Ash	AOCS Ck 2-09	0.00	% mass	Report
Glycerin	AOCS Ea 6-94	87.86	% mass	Report
Methanol	EN 14110	0.022	% mass	0.5%
Moisture	ASTM E203	11.668	% mass	Report
Density @20°C	ASTM D4052	1.2093	g/mL	Report
MONG	Calculation	0.5	% mass	Report
Soap	AOCS Cc 17-95	0	ppm	Report
pH	In House	3.60	IU	Report
Chloride	Photometric	119	ppm	Report

1. CHEMICAL PRODUCT

General Product Name: **Glycerin**

Synonyms: Propanetriol, 1,2,3-Propantriol

Product Description: Partially refined glycerol by-product of biodiesel process

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Primary Components</u>	<u>Composition</u>	<u>CAS No.</u>
Glycerin	75 – 90%	56-81-5
Water	5 – 20%	7732-18-5
Ash	0 – 1%	
Methanol	0.5% max	67-56-1

3. HAZARDS IDENTIFICATION

NFPA/HMIS Ratings: Health-1 Flammability-1 Reactivity-0

Potential Health Effects:

INHALATION: Negligible unless heated to produce vapors. Vapors or finely misted materials may irritate the mucous membranes and cause irritation, dizziness, and nausea. Remove to fresh air.

EYE CONTACT: May cause irritation. Irrigate eye with water for at least 15 to 20 minutes. Seek medical attention if symptoms persist.

SKIN CONTACT: Prolonged or repeated contact is not likely to cause significant skin irritation. Material is sometimes encountered at elevated temperatures. Thermal burns are possible.

INGESTION: No hazards anticipated from ingestion incidental to industrial exposure. May cause nausea, vomiting and diarrhea.

4. FIRST AID MEASURES

EYES: Irrigate eyes with a heavy stream of water for at least 15 to 20 minutes.

SKIN: Wash exposed areas of the body with soap and water.

INHALATION: Remove from area of exposure; seek medical attention if symptoms persist.

INGESTION: Give one or two glasses of water to drink. If gastro-intestinal symptoms develop, consult medical personnel. (Never give anything by mouth to an unconscious person.)

5. FIRE FIGHTING MEASURES

Flash Point (Method Used): > 130C (266F) (ASTM 93)

Flammability Limits: None known

EXTINGUISHING MEDIA: Dry chemical, foam, halon (may not be permissible in some countries), CO₂, water spray (fog). Water stream may splash the burning liquid and spread fire.

SPECIAL FIRE FIGHTING PROCEDURES: Use water spray to cool containers exposed to fire. Wear self-contained breathing apparatus for fire fighting.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Irritating and toxic gases or fumes may be released during a fire.

6. ACCIDENTAL RELEASE MEASURES SPILL CLEAN-UP PROCEDURES

Remove sources of ignition, contain spill to smallest area possible. Stop leak if possible. Pick up small spills with absorbent materials and dispose of properly to avoid spontaneous combustion (see unusual fire and explosion hazards above). Recover large spills for salvage or disposal. Wash hard surfaces with safety solvent or detergent to remove remaining oil film. Greasy nature will result in a slippery surface.

7. HANDLING AND STORAGE

Store in closed containers between 50°F and 120°F.

Keep away from oxidizing agents, excessive heat, and ignition sources.

Store and use in well ventilated areas.

Do not store or use near heat, spark, or flame, store out of sun.

Do not puncture, drag, or slide container.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

RESPIRATORY PROTECTION: If vapors or mists are generated, wear a NIOSH approved organic vapor/mist respirator.

PROTECTIVE CLOTHING: Safety glasses, goggles, or face shield recommended to protect eyes from mists or splashing. PVC coated gloves recommended to prevent skin contact.

OTHER PROTECTIVE MEASURES: Employees must practice good personal hygiene, washing exposed areas of skin several times daily and laundering contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point (760 mm Hg): Water and Methanol contamination will boil <110°C. Glycerin portion boils about 290°C with decomposition, possibly releasing acrolein.

Flash point: 160°C (320°F)

Volatiles (%v): <2

Specific Gravity (H₂O=1): 1.24 (approximate)

Solubility in H₂O (%v): 100 (miscible)

Vapor Pressure (mm Hg): <1

Evaporation Rate (Butyl Acetate=1): <1

Vapor Density (Air=1): 3.2

Appearance and Odor: deep gray-brown color, viscous liquid, bland to fatty odor

10. STABILITY AND REACTIVITY

GENERAL: This product is stable and hazardous polymerization will not occur.

INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID: Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion produces carbon monoxide, carbon dioxide along with thick smoke.

11. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Waste may be disposed of by a licensed waste disposal company. Contaminated absorbent material may be disposed of in an approved landfill. Follow local, state and federal disposal regulations.

12. TRANSPORT INFORMATION

US DOT: Not regulated as a hazardous material

UN HAZARD CLASS: N/A

PROPER SHIPPING NAME: Glycerin

13. REGULATORY INFORMATION:

OSHA STATUS: This product is not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200. However, thermal processing and decomposition fumes from this product may be hazardous as noted in Sections 5, 9 and 10.

TSCA STATUS: This product is listed on TSCA.

CERCLA (Comprehensive Response Compensation and Liability Act): NOT reportable.

SARA TITLE III (Superfund Amendments and Reauthorization Act): Section 312 Extremely Hazardous Substances: None

Section 311/312 Hazard Categories: Non-hazardous under Section 311/312

Section 313 Toxic Chemicals: None

RCRA STATUS: If discarded in its purchased form, this product would not be a hazardous waste either by listing or by characteristic. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste, (40 CFR 261.20-24)

CALIFORNIA PROPOSITION 65: The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986. This product contains no chemicals known to the state of California to cause cancer.

14. OTHER INFORMATION:

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. Such information is to the best of the company's knowledge and believed accurate and reliable as of the date indicated. However, no representation, warranty or guarantee of any kind, express or implied, is made as to its accuracy, reliability or completeness and we assume no responsibility for any loss, damage or expense, direct or consequential, arising out of use. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use.

CONTACT:

Solvent Systems International
70 King Street
Elk Grove Village, IL 60007

Phone:
847-437-1100

Date of last review: 11/15/2021