


Offer Sheet

Product	TEA (triethanolamine 99%)
Quantity	18 IBC totes x 296 gallons = 5,328 gallons
Net weight	39,683 lbs.
Manufacture date	MFG: 4/17/24 – EXP /17/27
Availability	One time
Location	North Charleston, SC 2940
Date	1/14/26
COA & SDS	Attached below



Brian Svrusis
Solvent Systems International
575 Bennett Road
Elk Grove Village, IL 60007
847-323-6718 call or text
Click here for: [Surplus Inventory](#)
Solvent-Systems.com



STARCHEM USA

CERTIFICATE OF ANALYSIS

INTERNAL REFERENCE

3210-OU102

Starchem USA
5689 NW 35th Ct
Miami, FL 33142
USA
(305) 859-1418

CUSTOMER PURCHASE ORDER
TBA

PRODUCT: Triethanolamine-H
CAS NUMBER: CAS No.102-71-6

PRODUCT CODE: TEA-H IBC
CLIENT PRODUCT CODE: TBA

LOT: 20240417

MFG. DATE: 4/17/2024
EXP. DATE: 4/17/2027

NOTE:

PARAMETER	RESULT
Water, WT%	0.28
Monoethanolamine, WT%	0.001
Diethanolamine, WT%	0.075
Triethanolamine, WT%	98.91
Appearance	BROWN

The information provided in this document is believed to be accurate and was obtained from sources believed to be reliable. However, the information is provided without any representation or warranty, expressed or implied, with respect to its accuracy or completeness. It is the user's responsibility to determine the suitability of this product and relevance of this information for its use. We do not assume liability resulting from the use, handling, storage, and disposal of this product.



SAFETY DATA SHEET

Product name: TRIETHANOLAMINE 99%

Issue Date: 03/11/2023

Starchem USA encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: TRIETHANOLAMINE 99%

Recommended use of the chemical and restrictions on use

Identified uses: Chemical intermediate Chemical additive.

COMPANY IDENTIFICATION

Starchem USA, LLC
5689 NW 35TH COURT
MIAMI, FL 33142
UNITED STATES

Customer Information Number: +1 281 414-8732

EMERGENCY TELEPHONE NUMBER

CHEMTREC®, Inside the USA: 800-424-9300

CHEMTREC®, Outside the USA: 001-703-527-3887

2. HAZARDS IDENTIFICATION

Hazard classification

This material is not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Other hazards

no data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms: alkanolamine

This product is a substance.

Component

CASRN

Concentration

Triethanolamine	102-71-6	> 99.0 %
N,N-Diethanolamine	111-42-2	<= 0.5 %

4. FIRST AID MEASURES

Description of first aid measures

General advice: First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Skin contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: No emergency medical treatment necessary.

Most important symptoms and effects, both acute and delayed: Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: If burn is present, treat as any thermal burn, after decontamination. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Unsuitable extinguishing media: Do not use direct water stream. May spread fire.

Special hazards arising from the substance or mixture

Hazardous combustion products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Nitrogen oxides. Carbon monoxide. Carbon dioxide.

Unusual Fire and Explosion Hazards: Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.

Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Burning liquids may be extinguished by dilution with water. Do not use direct water stream. May spread fire. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage.

Special protective equipment for firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Isolate area. Keep unnecessary and unprotected personnel from entering the area. Refer to section 7, Handling, for additional precautionary measures. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and materials for containment and cleaning up: Large spills: Dike area to contain spill. Pump into suitable and properly labeled containers. Small spills: Dilute with water. Recover spilled material if possible. Absorb with materials such as: Non-combustible material. Sand. Remove with shovel. Collect in suitable and properly labeled containers. Contain spilled material if possible. See Section 13, Disposal Considerations, for additional information.

7. HANDLING AND STORAGE

Precautions for safe handling: Thaw and mix well before using. Avoid contact with eyes. Wash thoroughly after handling. Do not use sodium nitrite or other nitrosating agents in formulations containing this product. Suspected cancer-causing nitrosamines could be formed. Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Conditions for safe storage: Avoid freezing. Store under an oxygen-free nitrogen atmosphere. Store in a dry place. Avoid moisture.

Storage stability

Storage temperature: 30 - 43 °C (86 - 109 °F)

Storage Period:, Metal drums., Plastic drums., Steel drums. 24 Month

Storage Period:, Bulk 6 Month

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits are listed below, if they exist.

Component	Regulation	Type of listing	Value/Notation
Triethanolamine	ACGIH	TWA	5 mg/m3
N,N-Diethanolamine	IHG	TWA	0.2 mg/m3
	IHG	TWA	Absorbed via skin
	ACGIH	TWA Inhalable fraction and vapor	1 mg/m3
	ACGIH	TWA	Absorbed via skin

Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use safety glasses (with side shields).

Skin protection

Hand protection: Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Examples of preferred glove barrier materials include: Chlorinated polyethylene. Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). Viton.

NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: When prolonged or frequently repeated contact could occur, use protective clothing chemically resistant to this material. Selection of specific items such as faceshield, boots, apron, or full-body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions no respiratory protection should be needed; however, if discomfort is experienced, use an approved air-purifying respirator.

The following should be effective types of air-purifying respirators: Organic vapor cartridge.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state Liquid.

Color Colorless to yellow

Odor Ammoniacal

Odor Threshold	No test data available
pH	No test data available
Melting point/range	Not applicable to liquids
Freezing point	20.5 °C (68.9 °F) <i>Literature</i>
Boiling point (760 mmHg)	336.1 °C (637.0 °F) at 1,013.25 hPa <i>Literature</i>
Flash point	closed cup 179 °C (354 °F) <i>Literature</i>
Evaporation Rate (Butyl Acetate = 1)	0.01 <i>Literature</i>
Flammability (solid, gas)	Not applicable to liquids
Lower explosion limit	No test data available
Upper explosion limit	No test data available
Vapor Pressure	< 0.0002 mmHg at 21 °C (70 °F) <i>Literature</i>
Relative Vapor Density (air = 1)	5 <i>Literature</i>
Relative Density (water = 1)	1.126 at 20 °C (68 °F) / 20 °C <i>Literature</i>
Water solubility	> 1000 g/L at 20 °C (68 °F) <i>Literature</i> Miscible in all proportions
Partition coefficient: n-octanol/water	log Pow: -2.3 <i>Measured</i>
Auto-ignition temperature	324 °C (615 °F) <i>Literature</i>
Decomposition temperature	No test data available
Dynamic Viscosity	934 mPa.s at 20 °C (68 °F) <i>Literature</i>
Kinematic Viscosity	No test data available
Explosive properties	No
Oxidizing properties	No
Liquid Density	1.125 g/cm ³ at 20 °C (68 °F) <i>Literature</i>
Molecular weight	149.19 g/mol <i>Literature</i>
Percent volatility	no data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: no data available

Chemical stability: Stable under recommended storage conditions. See Storage, Section 7. Hygroscopic

Possibility of hazardous reactions: Polymerization will not occur.

Conditions to avoid: Exposure to elevated temperatures can cause product to decompose. Generation of gas during decomposition can cause pressure in closed systems. Avoid moisture.

Incompatible materials: Avoid contact with: Nitrites. Strong acids. Strong oxidizers. Product may potentially react with various halogenated organic solvents, resulting in temperature and/or pressure increases. Corrosive when wet. Heating above 60°C in the presence of aluminum can result in corrosion and generation of flammable hydrogen gas. Avoid unintended contact with: Halogenated hydrocarbons.

Hazardous decomposition products: Decomposition products depend upon temperature, air supply and the presence of other materials.

11. TOXICOLOGICAL INFORMATION

Toxicological information on this product or its components appear in this section when such data is available.

Acute toxicity

Acute oral toxicity

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

LD50, Rat, 6,400 mg/kg

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

LD50, Rabbit, > 2,000 mg/kg No deaths occurred at this concentration.

Acute inhalation toxicity

At room temperature, exposure to vapor is minimal due to low volatility; single exposure is not likely to be hazardous. Based on the available data, respiratory irritation was not observed.

Skin corrosion/irritation

Brief contact is essentially nonirritating to skin.

Repeated exposure may cause irritation, even a burn.

Serious eye damage/eye irritation

May cause slight eye irritation.

Corneal injury is unlikely.

Sensitization

Skin contact may cause an allergic skin reaction in a small proportion of individuals.

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Carcinogenicity

Findings from a chronic skin painting study by NTP include liver tumors in mice. Mechanistic studies indicate that tumor formation is of questionable relevance to humans. Is not classified as a human carcinogen.

Teratogenicity

Has been toxic to the fetus in laboratory animals at doses toxic to the mother. However, the relevance of this to humans is unknown. Dose levels producing these effects were many times higher than any dose levels expected from exposure due to use.

Reproductive toxicity

No relevant data found.

Mutagenicity

In vitro genetic toxicity studies were negative.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

COMPONENTS INFLUENCING TOXICOLOGY:**Triethanolamine****Acute inhalation toxicity**

Based on the available data, respiratory irritation was not observed. No deaths occurred following exposure to a saturated atmosphere.

N,N-Diethanolamine**Acute inhalation toxicity**

LC0, Rat, male, 4 Hour, Aerosol, 3.35 mg/l

Carcinogenicity**Component****N,N-Diethanolamine****List**

IARC

Classification

Group 2B: Possibly carcinogenic to humans

ACGIH

A3: Confirmed animal carcinogen with unknown relevance to humans.

12. ECOLOGICAL INFORMATION

Ecotoxicological information on this product or its components appear in this section when such data is available.

Toxicity**Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

May increase pH of aquatic systems to > pH 10 which may be toxic to aquatic organisms.

LC50, Pimephales promelas (fathead minnow), flow-through test, 96 Hour, 11,800 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Ceriodaphnia dubia (water flea), static test, 48 Hour, 609.9 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

ErC50, alga Scenedesmus sp., static test, 72 Hour, Growth rate inhibition, 512 mg/l, OECD Test Guideline 201 or Equivalent, Test substance: Neutralised product

Toxicity to bacteria

EC50, activated sludge, 3 Hour, > 1,000 mg/l, OECD 209 Test

Chronic aquatic toxicity**Chronic toxicity to aquatic invertebrates**

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, 16 mg/l

LOEC, Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, 31 mg/l

Persistence and degradability

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability. Material is ultimately biodegradable (reaches > 70% mineralization in OECD test(s) for inherent biodegradability).

10-day Window: Pass

Biodegradation: 97 %

Exposure time: 28 d

Method: OECD Test Guideline 301A or Equivalent

10-day Window: Not applicable

Biodegradation: 89 %

Exposure time: 14 d

Method: OECD Test Guideline 302B or Equivalent

Theoretical Oxygen Demand: 2.04 mg/mg

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitizer: OH radicals

Atmospheric half-life: 0.097 d

Method: Estimated.

Bioaccumulative potential

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): -2.3 at 25 °C Measured

Bioconcentration factor (BCF): < 3.9 Cyprinus carpio (Carp) 42 d Measured

Mobility in soil

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient(Koc): 10 Estimated.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and

compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device.

14. TRANSPORT INFORMATION

DOT

Proper shipping name	Environmentally hazardous substance, liquid, n.o.s.(Diethanolamine)
UN number	UN 3082
Class	9
Packing group	III
Reportable Quantity	Diethanolamine

Classification for SEA transport (IMO-IMDG):

Transport in bulk	Not regulated for transport
according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code	Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

OSHA Hazard Communication Standard

This product is not a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

This product is not a hazardous chemical under 29CFR 1910.1200, and therefore is not covered by Title III of SARA.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Pennsylvania Worker and Community Right-To-Know Act:

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

WARNING: This product contains a chemical(s) known to the State of California to cause cancer.

Components**CASRN**

N,N-Diethanolamine

111-42-2

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

:

16. OTHER INFORMATION

Product Literature

Additional information on this product may be obtained by calling your sales or customer service contact. Ask for a product brochure. Additional information on this and other products may be obtained by visiting our web page.

Hazard Rating System**NFPA**

Health	Fire	Reactivity
1	1	0

Legend

Absorbed via skin	Absorbed via skin
ACGIH	USA. ACGIH Threshold Limit Values (TLV)
IHG	Industrial Hygiene Guideline
TWA	8-hour, time-weighted average

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

Starchem USA, LLC urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.